

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Issue date: 9/23/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : MAPLE SYRUP & PANCAKES FR98009

Product code : FR98009

Type of product : Perfumes, fragrances Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

: Professional use Industrial use Main use category

Industrial/Professional use spec · Industrial

For professional use only Use of the substance/mixture : Perfumes, fragrances Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Hyggeland Company Russian Federation Krasnodar

Stasova 184, 7

Phone .: +7 (953) 073-39-63

info@hyggeland.ru https://hyggeland.ru/

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H317 Skin sensitisation, Category 1 Hazardous to the aquatic environment – Acute Hazard, H400

Category 1

Hazardous to the aquatic environment - Chronic Hazard, H411

Category 2

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS07

GHS09

Safety Data Sheet

Precautionary statements (CLP)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Signal word (CLP) : Warning

Contains : benzyl benzoate; 1,2-Cyclopentanedione, 3-methyl-

Hazard statements (CLP) : H302 - Harmful if swallowed.

H317 - May cause an allergic skin reaction.

H410 - Very toxic to aquatic life with long lasting effects.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

Extra phrases : For professional users only.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|---|--|-------------------|---|
| benzyl benzoate | CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33 | 43.1 – 86.2999 | Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 |
| Vanillin | CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040- 60 | 2.512 – 5.045 | Eye Irrit. 2, H319 |
| 1,2-Cyclopentanedione, 3-methyl- | CAS-No.: 765-70-8 EC-No.: 212-154-8 | 0.9 – 1.75 | Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317 |
| Ethyl vanillin | CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24 | 0.8 – 1.5 | Eye Irrit. 2, H319 |
| pentyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit | CAS-No.: 628-63-7 EC-No.: 211-047-3 EC Index-No.: 607-130-00-2 | 0.4 – 0.8125 | Flam. Liq. 3, H226 |
| isopentyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit | CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408- 32 | 0.3 – 0.5625 | Flam. Liq. 3, H226 |

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|--|---------------|--|
| Butylated hydroxytoluene (BHT) crystals substance with national workplace exposure limit(s) (AT, BE, BG, DE, DK, ES, FI, FR, GB, GR, HR, IE, PT, SI, CH) | CAS-No.: 128-37-0 EC-No.: 204-881-4 REACH-no: 01-2119480433- 40 | 0.2 – 0.375 | Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| butyric acid substance with national workplace exposure limit(s) (BG, LT, LV, RO) | CAS-No.: 107-92-6 EC-No.: 203-532-3 EC Index-No.: 607-135-00-X | 0 – 0.0625 | Skin Corr. 1B, H314 |
| 1,2-Propanediol substance with national workplace exposure limit(s) (GB, HR, IE, LT, LV, PL, NO) | CAS-No.: 57-55-6 EC-No.: 200-338-0 REACH-no: 01-2119456809- 23 | 0.012 – 0.045 | Not classified |
| Isoamyl alcohol substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR) | CAS-No.: 123-51-3 EC-No.: 204-633-5 | 0 – 0.0125 | Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 |

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a poison center or a doctor if you feel unwell. First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing. Allow affected person to

breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/.... Get medical advice/attention. Wash contaminated clothing before reuse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness First-aid measures after eye contact persists. Rinse eyes with water as a precaution.

First-aid measures after ingestion Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Do not use a heavy water stream. Unsuitable extinguishing media

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

9/23/2024 (Issue date) EN (English) 3/28

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew

with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep

container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

Germany

Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids

9/23/2024 (Issue date) EN (English) 4/28

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Joint storage table LGK 1 LGK 2A LGK 2B LGK 3 LGK 4.1A LGK 4.1B LGK 4.2 LGK 4.3 LGK 5.1A LGK 5.1B LGK 6.1A LGK 6.1B LGK 5.1C LGK 5.2 LGK 6.1C LGK 6.1D LGK 6.2 LGK 7 LGK 8A LGK 8B LGK 11 LGK 12 LGK 10 LGK 13 LGK 10-13

Joint storage not permitted for : LGK 1, LGK 6.2, LGK 7

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.3, LGK 5.1C

Joint storage permitted for : LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A,

LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK

10-13

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

| 1,2-Propanediol (57-55-6) | | |
|---|---|--|
| Croatia - Occupational Exposure Limits | | |
| GVI (OEL TWA) | 474 mg/m³ (total vapor and particles) 10 mg/m³ (particles) | |
| | 150 ppm | |
| Ireland - Occupational Exposure Limits | | |
| OEL TWA | 10 mg/m³ (particulates) 470 mg/m³ (total vapour and particulates) | |
| | 150 ppm (total vapour and particulates) | |
| OEL STEL | 1410 mg/m³ (calculated-particulates) 30 mg/m³ (calculated) | |
| | 450 ppm (calculated-total vapour and particulates) | |
| Latvia - Occupational Exposure Limits | | |
| OEL TWA | 7 mg/m³ | |
| Lithuania - Occupational Exposure Limits | | |
| IPRV (OEL TWA) | 7 mg/m³ | |
| Poland - Occupational Exposure Limits | | |
| NDS (OEL TWA) | 100 mg/m³ (vapor and inhalable fraction) | |
| United Kingdom - Occupational Exposure Limits | | |
| WEL TWA (OEL TWA) | 474 mg/m³ (total vapour and particulates) 10 mg/m³ (particulates) | |
| | 150 ppm (total vapour and particulates) | |
| WEL STEL (OEL STEL) | 1422 mg/m³ (calculated-total vapour and particulates) 30 mg/m³ (calculated-particulate) | |
| | 450 ppm (calculated-total vapour and particulates) | |

Safety Data Sheet

| 1,2-Propanediol (57-55-6) | | |
|---|--|--|
| Norway - Occupational Exposure Limits | | |
| Grenseverdi (OEL TWA) | 79 mg/m³ | |
| | 25 ppm | |
| Korttidsverdi (OEL STEL) | 118.5 mg/m³ (value calculated) | |
| | 37.5 ppm (value calculated) | |
| pentyl acetate (628-63-7) | | |
| EU - Indicative Occupational Exposure Limit (IOEL | -) | |
| IOEL TWA | 270 mg/m³ | |
| | 50 ppm | |
| IOEL STEL | 540 mg/m³ | |
| | 100 ppm | |
| Austria - Occupational Exposure Limits | | |
| MAK (OEL TWA) | 270 mg/m³ (Pentyl acetate (all isomers)) | |
| | 50 ppm (Pentyl acetate (all isomers)) | |
| MAK (OEL STEL) | 540 mg/m³ (Pentylacetate) | |
| | 100 ppm (Pentylacetate) | |
| Belgium - Occupational Exposure Limits | | |
| OEL TWA | 270 mg/m³ | |
| | 50 ppm | |
| OEL STEL | 540 mg/m³ | |
| | 100 ppm | |
| Bulgaria - Occupational Exposure Limits | | |
| OEL TWA | 270 mg/m³ | |
| | 50 ppm | |
| OEL STEL | 540 mg/m³ | |
| | 100 ppm | |
| Croatia - Occupational Exposure Limits | | |
| GVI (OEL TWA) | 270 mg/m³ | |
| | 50 ppm | |
| KGVI (OEL STEL) | 540 mg/m³ | |
| | 100 ppm | |
| Cyprus - Occupational Exposure Limits | | |
| OEL TWA | 270 mg/m³ | |
| | 50 ppm | |
| OEL STEL | 540 mg/m³ | |
| | 100 ppm | |
| Denmark - Occupational Exposure Limits | | |
| OEL TWA | 271 mg/m³ (Amyl acetate, all isomers) | |
| | 50 ppm (Amyl acetate, all isomers) | |
| | | |

Safety Data Sheet

| OEL STEL \$40 mg/m² Finiand - Occupational Exposure Limits 270 mg/m² (Pentyl acetate) HTP (OEL TWA) \$40 mg/m² HTP (OEL STEL) \$40 mg/m² Fance - Occupational Exposure Limits 270 mg/m² (restrictve limit) VLE (OEL CYSTEL) \$40 mg/m² (restrictve limit) OCCUPATIONAL \$40 | pentyl acetate (628-63-7) | |
|--|--|---------------------------------------|
| Finiand - Occupational Exposure Limits HTP (OEL TWA) 270 mg/m³ (Pentyl acetate) 50 ppm (Pentyl acetate) 50 ppm (Pentyl acetate) France - Occupational Exposure Limits 270 mg/m³ (restrictive limit) VME (OEL TWA) 270 mg/m³ (restrictive limit) 50 ppm (restrictive limit) 50 ppm (restrictive limit) Commany - Occupational Exposure Limits (TRGS #0000) A GWY (OEL TWA) 270 mg/m³ (restrictive limit) B GWY acitasa are observed) | OEL STEL | 540 mg/m³ |
| HTP (OEL TWA) 270 mg/m² (Pentyl acetate) HTP (OEL STEL) 540 mg/m² 100 ppm 100 ppm France - Occupational Exposure Limits VME (OEL TWA) 270 mg/m² (restrictive limit) 540 mg/m² (restrictive limit) 540 mg/m² (restrictive limit) Occupational Exposure Limits (TRGS#*) To mg/m² (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Gibraltar - Occupational Exposure Limits To mg/m² (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Gibraltar - Occupational Exposure Limits To mg/m² (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Gibraltar - Occupational Exposure Limits To pg/m² Oppm Oppm Del TWA 50 ppm Oppm Numary - Occupational Exposure Limits To pg/m² Oppm Del TWA 270 mg/m² Oppm Oppm <td></td> <td>100 ppm</td> | | 100 ppm |
| BMTP (OEL STEL) 50 pm(Pentyl acetate) 540 mg/m² 7 mace - Occupational Exposure Limits YME (OEL CYSTEL) 270 mg/m² (restrictive limit) 540 mg/m² (restrictive limit) 540 mg/m² (restrictive limit) 540 mg/m² (restrictive limit) 7 mg/m² (restrictive limit) 7 mg/m² (restrictive limit) 7 mg/m² (restrictive limit) 7 mg/m² (restrictive limit) 8 mg/m² (restrictive limit) 9 mg/m² (restrictive limit) | Finland - Occupational Exposure Limits | |
| HTP (OEL STEL) \$40 mg/m² France - Occupational Exposure Limits 270 mg/m² (restrictive limit) VME (OEL TWA) 270 mg/m² (restrictive limit) VLE (OEL C/STEL) \$40 mg/m² (restrictive limit) Corrupational Exposure Limits (TRGS 9000000000000000000000000000000000000 | HTP (OEL TWA) | 270 mg/m³ (Pentyl acetate) |
| France - Occupational Exposure Limits YME (OEL CISTEL) 270 mg/m² (restrictive limit) 50 pm (restrictive limit) 100 ppm (restrictive limit) 100 ppm (restrictive limit) 60 crmany - Occupational Exposure Limits (TRGS ***) AGW (OEL TWA) 270 mg/m² (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 80 ppm (he risk of damage to the embr | | 50 ppm (Pentyl acetate) |
| France - Occupational Exposure Limits VME (OEL TWA) 270 mg/m³ (restrictive limit) VLE (OEL C/STEL) 540 mg/m³ (restrictive limit) OE OFFICIAL TWA) 450 mg/m³ (restrictive limit) OE OFFICIAL TWA) 270 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BCW values are observed) Figuratur - Occupational Exposure Limits 270 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BCW values are observed) Gibraltur - Occupational Exposure Limits 270 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BCW values are observed) Gibraltur - Occupational Exposure Limits 270 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BCW values are observed) Gibraltur - Occupational Exposure Limits 270 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BCW values are observed) Gibraltur - Occupational Exposure Limits 270 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BCW values are observed) Gibraltur - Occupational Exposure Limits 800 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BCW values are observed) Gibraltur - Occupational Exposure Limits 800 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BCW values are observed) Gibraltur - Occupational Exposure Limits 270 mg/m³ (the risk of damage to the | HTP (OEL STEL) | 540 mg/m³ |
| VME (OEL CYSTEL) 270 mg/m² (restrictive limit) VLE (OEL CYSTEL) 540 mg/m² (restrictive limit) OErmany - Occupational Exposure Limits (TRGS) 700 mg/m² (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) 270 mg/m² (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Gibraltar - Occupational Exposure Limits 270 mg/m² GE TWA 270 mg/m² 50 ppm 50 ppm Genece - Occupational Exposure Limits 50 ppm Greece - Occupational Exposure Limits 50 ppm Hungary - Occupational Exposure Limits 50 ppm Hungary - Occupational Exposure Limits 50 ppm CK (OEL STEL) 540 mg/m² Ireland - Occupational Exposure Limits 50 ppm OEL TWA 270 mg/m² 60 ppm 50 ppm OEL TWA 60 ppm 61 ppm 100 ppm Total ppm 100 ppm | | 100 ppm |
| New (Pectric (Pect | France - Occupational Exposure Limits | |
| VLE (OEL CYSTEL) \$40 mg/m² (restrictive limit) Germany - Occupational Exposure Limits (TRGS 9000) \$270 mg/m² (the risk of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded when AGW and Back of damage to the embryo or fetus can be excluded and Back of damage to the embryo or fetus can be excluded when AG | VME (OEL TWA) | 270 mg/m³ (restrictive limit) |
| Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) 270 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Gibraltar - Occupational Exposure Limits 270 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Gibraltar - Occupational Exposure Limits 270 mg/m³ OEL STEL 50 ppm Greece - Occupational Exposure Limits 530 mg/m³ OEL TWA 530 mg/m³ 100 ppm 100 ppm OEL STEL 800 mg/m³ 100 ppm 100 ppm Hungary - Occupational Exposure Limits 800 mg/m³ K (OEL TWA) 270 mg/m³ CK (OEL STEL) 50 ppm Ireland - Occupational Exposure Limits 40 mg/m³ OEL TWA 50 ppm OEL STEL 40 mg/m³ 100 ppm 100 ppm CEL TWA 270 mg/m³ OEL STEL 50 ppm OEL STEL 270 mg/m³ 100 ppm 100 ppm CEL TWA 270 mg/m³ 50 | | 50 ppm (restrictive limit) |
| Germany - Occupational Exposure Limits (TRGS 90) AGW (OEL TWA) 270 mg/m² (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) GEL TWA 270 mg/m² 50 ppm CEL TWA 270 mg/m² 50 ppm GEL TWA 530 mg/m² 600 ppm 601 ppm CEL STEL 800 mg/m² 602 ppm CHURGAN (OEL TWA) 800 mg/m² 603 ppm CHURGAN (OEL TWA) 270 mg/m² 604 0 mg/m² CH TWA 270 mg/m² 604 0 mg/m² 605 ppm 606 DEL STEL 540 mg/m² 607 ppm 608 DEL STEL 540 mg/m² 609 ppm 618 DEL TWA 270 mg/m² 620 ppm 621 TWA 270 mg/m² 630 ppm 641 Del TWA 270 mg/m² 652 ppm 653 ppm 654 ppm 654 ppm 655 ppm 656 ppm 657 ppm 658 ppm 659 ppm 650 ppm <td>VLE (OEL C/STEL)</td> <td>540 mg/m³ (restrictive limit)</td> | VLE (OEL C/STEL) | 540 mg/m³ (restrictive limit) |
| AGW (OEL TWA) 270 mg/m² (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) GIbraitar - Occupational Exposure Limits OEL TWA 270 mg/m² 50 ppm 540 mg/m³ 100 ppm 60 ppm Greece - Occupational Exposure Limits 530 mg/m³ 0EL TWA 530 mg/m³ 100 ppm 60 mg/m³ 150 ppm Hungary - Occupational Exposure Limits 800 mg/m³ AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ 100 ppm 100 ppm OEL STEL 540 mg/m³ 50 ppm 50 ppm OEL TWA 540 mg/m³ | | 100 ppm (restrictive limit) |
| BGW values are observed 50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) | Germany - Occupational Exposure Limits (TRGS 9 | 00) |
| Values are observed Values are observed | AGW (OEL TWA) | |
| OEL TWA 270 mg/m³ 50 ppm 540 mg/m³ OEL STEL 540 mg/m³ 0 ppm 670 mg/m³ Greece - Occupational Exposure Limits OEL TWA 530 mg/m³ 100 ppm 600 mg/m³ 150 ppm 700 mg/m³ Hungary - Occupational Exposure Limits AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm 640 mg/m³ Italy - Occupational Exposure Limits OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL TWA 60 ppm | | , , , , , , , , , , , , , , , , , , , |
| S0 ppm | Gibraltar - Occupational Exposure Limits | |
| OEL STEL 540 mg/m³ 100 ppm 100 ppm Greece - Occupational Exposure Limits 530 mg/m³ 0EL TWA 530 mg/m³ 100 ppm 800 mg/m³ 150 ppm Hungary - Occupational Exposure Limits AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ 0EL TEL 540 mg/m³ 100 ppm Italy - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ 0EL TWA 270 mg/m³ | OEL TWA | 270 mg/m³ |
| 100 ppm | | 50 ppm |
| Greece - Occupational Exposure Limits OEL TWA 530 mg/m³ 100 ppm 6800 mg/m³ 150 ppm 150 ppm Hungary - Occupational Exposure Limits AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ Italy - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 50 ppm OEL STEL 540 mg/m³ | OEL STEL | 540 mg/m³ |
| OEL TWA 530 mg/m³ 100 ppm 100 ppm OEL STEL 800 mg/m³ 150 ppm 150 ppm Hungary - Occupational Exposure Limits AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ Italy - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ | | 100 ppm |
| 100 ppm 100 ppm 100 ppm 100 ppm 100 ppm 150 ppm 15 | Greece - Occupational Exposure Limits | |
| OEL STEL 800 mg/m³ Hungary - Occupational Exposure Limits AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ Italy - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ | OEL TWA | 530 mg/m³ |
| Toppm Topp | | 100 ppm |
| Hungary - Occupational Exposure Limits | OEL STEL | 800 mg/m³ |
| AK (OEL TWA) CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm Italy - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 50 ppm OEL TWA 550 ppm OEL STEL 540 mg/m³ 50 ppm OEL STEL | | 150 ppm |
| CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm Italy - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ | Hungary - Occupational Exposure Limits | |
| Ireland - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm 540 mg/m³ 100 ppm 100 ppm Italy - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm 540 mg/m³ OEL STEL 540 mg/m³ | AK (OEL TWA) | 270 mg/m³ |
| OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm Italy - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ | CK (OEL STEL) | 540 mg/m³ |
| State | Ireland - Occupational Exposure Limits | |
| OEL STEL 540 mg/m³ 100 ppm Italy - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ | OEL TWA | 270 mg/m³ |
| 100 ppm 100 ppm | | 50 ppm |
| Italy - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ | OEL STEL | 540 mg/m³ |
| OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ | | 100 ppm |
| 50 ppm OEL STEL 540 mg/m³ | Italy - Occupational Exposure Limits | • |
| OEL STEL 540 mg/m³ | OEL TWA | 270 mg/m³ |
| | | 50 ppm |
| 100 ppm | OEL STEL | 540 mg/m³ |
| | | 100 ppm |

Safety Data Sheet

| pentyl acetate (628-63-7) | |
|--|--|
| Latvia - Occupational Exposure Limits | |
| OEL TWA | 270 mg/m³ |
| | 50 ppm |
| Lithuania - Occupational Exposure Limits | |
| IPRV (OEL TWA) | 270 mg/m³ (except tert-Amyl acetate (Pentyl acetate) |
| | 50 ppm (except tert-Amyl acetate (Pentyl acetate) |
| TPRV (OEL STEL) | 540 mg/m³ (regulated under Pentyl acetate (Pentyl acetate) |
| | 100 ppm (regulated under Pentyl acetate (Pentyl acetate) |
| Luxembourg - Occupational Exposure Limits | |
| OEL TWA | 270 mg/m³ |
| | 50 ppm |
| OEL STEL | 540 mg/m³ |
| | 100 ppm |
| Malta - Occupational Exposure Limits | |
| OEL TWA | 270 mg/m³ |
| | 50 ppm |
| OEL STEL | 540 mg/m³ |
| | 100 ppm |
| Netherlands - Occupational Exposure Limits | |
| TGG-15min (OEL STEL) | 530 mg/m³ |
| | 98.1 ppm |
| Poland - Occupational Exposure Limits | |
| NDS (OEL TWA) | 250 mg/m³ |
| NDSCh (OEL STEL) | 500 mg/m³ |
| Portugal - Occupational Exposure Limits | |
| OEL TWA | 270 mg/m³ (indicative limit value) |
| | 50 ppm (indicative limit value) |
| OEL STEL | 540 mg/m³ (indicative limit value) |
| | 100 ppm (indicative limit value) |
| Romania - Occupational Exposure Limits | |
| OEL TWA | 270 mg/m³ |
| | 50 ppm |
| OEL STEL | 540 mg/m³ |
| | 100 ppm |
| Slovakia - Occupational Exposure Limits | |
| NPHV (OEL TWA) | 270 mg/m³ |
| | 50 ppm |
| NPHV (OEL C) | 540 mg/m³ |

Safety Data Sheet

| Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ Spain - Occupational Exposure Limits VLA-ED (OEL TWA) 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) VLA-EC (OEL STEL) 540 mg/m³ 100 ppm Sweden - Occupational Exposure Limits | | |
|---|--|--|
| 50 ppm 50 ppm 540 mg/m³ 100 ppm | | |
| OEL STEL 540 mg/m³ 100 ppm Spain - Occupational Exposure Limits VLA-ED (OEL TWA) 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) VLA-EC (OEL STEL) 540 mg/m³ 100 ppm | | |
| Spain - Occupational Exposure Limits | | |
| Spain - Occupational Exposure Limits VLA-ED (OEL TWA) 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) VLA-EC (OEL STEL) 540 mg/m³ 100 ppm | | |
| VLA-ED (OEL TWA) 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) VLA-EC (OEL STEL) 540 mg/m³ 100 ppm | | |
| 50 ppm (indicative limit value) VLA-EC (OEL STEL) 540 mg/m³ 100 ppm | | |
| VLA-EC (OEL STEL) 540 mg/m³ 100 ppm | | |
| 100 ppm | | |
| | | |
| Sweden - Occupational Exposure Limits | | |
| | | |
| NGV (OEL TWA) 270 mg/m³ (Pentyl acetates) | | |
| 50 ppm (Pentyl acetates) | | |
| KGV (OEL STEL) 540 mg/m³ (Pentyl acetates) | | |
| 100 ppm (Pentyl acetates) | | |
| Norway - Occupational Exposure Limits | | |
| Grenseverdi (OEL TWA) 260 mg/m³ | | |
| 50 ppm | | |
| Korttidsverdi (OEL STEL) 325 mg/m³ (value calculated) | | |
| 75 ppm (value calculated) | | |
| Switzerland - Occupational Exposure Limits | | |
| MAK (OEL TWA) 260 mg/m³ (Pentyl acetate all isomers) | | |
| 50 ppm (Pentyl acetate all isomers) | | |
| KZGW (OEL STEL) 260 mg/m³ (Pentyl acetate all isomers) | | |
| 50 ppm (Pentyl acetate all isomers) | | |
| USA - ACGIH - Occupational Exposure Limits | | |
| ACGIH OEL TWA 50 ppm (Pentyl acetate, all isomers) | | |
| ACGIH OEL STEL 100 ppm (Pentyl acetate, all isomers) | | |
| isopentyl acetate (123-92-2) | | |
| EU - Indicative Occupational Exposure Limit (IOEL) | | |
| IOEL TWA 270 mg/m³ | | |
| 50 ppm | | |
| IOEL STEL 540 mg/m³ | | |
| 100 ppm | | |
| Austria - Occupational Exposure Limits | | |
| MAK (OEL TWA) 270 mg/m³ (Pentyl acetate (all isomers)) | | |
| 50 ppm (Pentyl acetate (all isomers)) | | |
| MAK (OEL STEL) 540 mg/m³ (Pentylacetate) | | |
| 100 ppm (Pentylacetate) | | |

Safety Data Sheet

| isopentyl acetate (123-92-2) | | |
|---|---------------------------------------|--|
| Belgium - Occupational Exposure Limits | | |
| OEL TWA | 270 mg/m³ | |
| | 50 ppm | |
| OEL STEL | 540 mg/m³ | |
| | 100 ppm | |
| Bulgaria - Occupational Exposure Limits | | |
| OEL TWA | 270 mg/m³ | |
| | 50 ppm | |
| OEL STEL | 540 mg/m³ | |
| | 100 ppm | |
| Croatia - Occupational Exposure Limits | | |
| GVI (OEL TWA) | 270 mg/m³ | |
| | 50 ppm | |
| KGVI (OEL STEL) | 540 mg/m³ | |
| | 100 ppm | |
| Cyprus - Occupational Exposure Limits | | |
| OEL TWA | 270 mg/m³ | |
| | 50 ppm | |
| OEL STEL | 540 mg/m³ | |
| | 100 ppm | |
| Denmark - Occupational Exposure Limits | | |
| OEL TWA | 271 mg/m³ (Amyl acetate, all isomers) | |
| | 50 ppm (Amyl acetate, all isomers) | |
| OEL STEL | 540 mg/m³ | |
| | 100 ppm | |
| Estonia - Occupational Exposure Limits | | |
| OEL TWA | 270 mg/m³ | |
| | 50 ppm | |
| OEL STEL | 540 mg/m³ | |
| | 100 ppm | |
| Finland - Occupational Exposure Limits | | |
| HTP (OEL TWA) | 270 mg/m³ (Pentyl acetate) | |
| , | 50 ppm (Pentyl acetate) | |
| HTP (OEL STEL) | 540 mg/m³ | |
| , | 100 ppm | |
| France - Occupational Exposure Limits | | |
| VME (OEL TWA) | 270 mg/m³ (restrictive limit) | |
| (, | 50 ppm (restrictive limit) | |
| VLE (OEL C/STEL) | 540 mg/m³ (restrictive limit) | |
| | g, () | |

Safety Data Sheet

| isopentyl acetate (123-92-2) | | |
|---|-----------------------------|--|
| | 100 ppm (restrictive limit) | |
| Germany - Occupational Exposure Limits (TRGS 90 | 00) | |
| AGW (OEL TWA) | 270 mg/m³ | |
| | 50 ppm | |
| Gibraltar - Occupational Exposure Limits | | |
| OEL TWA | 270 mg/m³ | |
| | 50 ppm | |
| OEL STEL | 540 mg/m³ | |
| | 100 ppm | |
| Greece - Occupational Exposure Limits | | |
| OEL TWA | 530 mg/m³ | |
| | 100 ppm | |
| OEL STEL | 800 mg/m³ | |
| | 150 ppm | |
| Hungary - Occupational Exposure Limits | | |
| AK (OEL TWA) | 270 mg/m³ | |
| CK (OEL STEL) | 540 mg/m³ | |
| Ireland - Occupational Exposure Limits | | |
| OEL TWA | 260 mg/m³ | |
| | 50 ppm | |
| OEL STEL | 520 mg/m³ | |
| | 100 ppm | |
| Italy - Occupational Exposure Limits | | |
| OEL TWA | 270 mg/m³ | |
| | 50 ppm | |
| OEL STEL | 540 mg/m³ | |
| | 100 ppm | |
| Latvia - Occupational Exposure Limits | | |
| OEL TWA | 270 mg/m³ | |
| | 50 ppm | |
| Lithuania - Occupational Exposure Limits | | |
| IPRV (OEL TWA) | 270 mg/m³ | |
| | 50 ppm | |
| TPRV (OEL STEL) | 540 mg/m³ | |
| | 100 ppm | |
| Luxembourg - Occupational Exposure Limits | | |
| OEL TWA | 270 mg/m³ | |
| | 50 ppm | |
| OEL STEL | 540 mg/m³ | |

Safety Data Sheet

| isopentyl acetate (123-92-2) | |
|--|--|
| | 100 ppm |
| Malta - Occupational Exposure Limits | |
| OEL TWA | 270 mg/m³ |
| | 50 ppm |
| OEL STEL | 540 mg/m³ |
| | 100 ppm |
| Netherlands - Occupational Exposure Limits | |
| TGG-15min (OEL STEL) | 530 mg/m³ |
| | 98.1 ppm |
| Poland - Occupational Exposure Limits | |
| NDS (OEL TWA) | 250 mg/m³ |
| NDSCh (OEL STEL) | 500 mg/m³ |
| Portugal - Occupational Exposure Limits | |
| OEL TWA | 270 mg/m³ (indicative limit value) |
| | 50 ppm (indicative limit value (Pentyl acetate, all isomers) |
| OEL STEL | 540 mg/m³ (indicative limit value) |
| | 100 ppm (indicative limit value) |
| Romania - Occupational Exposure Limits | |
| OEL TWA | 270 mg/m³ |
| | 50 ppm |
| OEL STEL | 540 mg/m³ |
| | 100 ppm |
| Slovakia - Occupational Exposure Limits | |
| NPHV (OEL TWA) | 270 mg/m³ |
| | 50 ppm |
| NPHV (OEL C) | 540 mg/m³ |
| Slovenia - Occupational Exposure Limits | |
| OEL TWA | 270 mg/m³ |
| | 50 ppm |
| OEL STEL | 540 mg/m³ |
| | 100 ppm |
| Spain - Occupational Exposure Limits | |
| VLA-ED (OEL TWA) | 270 mg/m³ (indicative limit value) |
| | 50 ppm (indicative limit value) |
| VLA-EC (OEL STEL) | 540 mg/m³ |
| | 100 ppm |
| Sweden - Occupational Exposure Limits | |
| NGV (OEL TWA) | 270 mg/m³ (Pentyl acetates) |
| | 50 ppm (Pentyl acetates) |

Safety Data Sheet

| isopentyl acetate (123-92-2) | | |
|--|--|--|
| KGV (OEL STEL) | 540 mg/m³ (Pentyl acetates) | |
| | 100 ppm (Pentyl acetates) | |
| Norway - Occupational Exposure Limits | | |
| Grenseverdi (OEL TWA) | 260 mg/m³ | |
| | 50 ppm | |
| Korttidsverdi (OEL STEL) | 325 mg/m³ (value calculated) | |
| | 75 ppm (value calculated) | |
| Switzerland - Occupational Exposure Limits | | |
| MAK (OEL TWA) | 260 mg/m³ (Pentyl acetate all isomers) | |
| | 50 ppm (Pentyl acetate all isomers) | |
| KZGW (OEL STEL) | 260 mg/m³ (Pentyl acetate all isomers) | |
| | 50 ppm (Pentyl acetate all isomers) | |
| USA - ACGIH - Occupational Exposure Limits | 1 | |
| ACGIH OEL TWA | 50 ppm (Pentyl acetate, all isomers) | |
| ACGIH OEL STEL | 100 ppm (Pentyl acetate, all isomers) | |
| Butylated hydroxytoluene (BHT) crystals (128 | 3-37-0) | |
| Austria - Occupational Exposure Limits | | |
| MAK (OEL TWA) | 10 mg/m³ | |
| Belgium - Occupational Exposure Limits | | |
| OEL TWA | 2 mg/m³ (aerosol and vapor) | |
| Bulgaria - Occupational Exposure Limits | | |
| OEL TWA | 10 mg/m³ | |
| OEL STEL | 50 mg/m³ | |
| Croatia - Occupational Exposure Limits | | |
| GVI (OEL TWA) | 10 mg/m³ | |
| Denmark - Occupational Exposure Limits | | |
| OEL TWA | 10 mg/m³ | |
| OEL STEL | 20 mg/m³ | |
| Finland - Occupational Exposure Limits | | |
| HTP (OEL TWA) | 10 mg/m³ | |
| HTP (OEL STEL) | 20 mg/m³ | |
| France - Occupational Exposure Limits | | |
| VME (OEL TWA) | 10 mg/m³ | |
| Germany - Occupational Exposure Limits (TRGS 9 | 00) | |
| AGW (OEL TWA) | 10 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-inhalable fraction) | |
| Greece - Occupational Exposure Limits | | |
| OEL TWA | 10 mg/m³ | |

Safety Data Sheet

| Butylated hydroxytoluene (BHT) crystals (128-37-0) | | |
|--|---|--|
| Ireland - Occupational Exposure Limits | | |
| OEL TWA | 2 mg/m³ | |
| OEL STEL | 6 mg/m³ (calculated) | |
| Portugal - Occupational Exposure Limits | | |
| OEL TWA | 2 mg/m³ (inhalable fraction; vapor) | |
| OEL chemical category | A4 - Not Classifiable as a Human Carcinogen | |
| Slovenia - Occupational Exposure Limits | | |
| OEL TWA | 10 mg/m³ (inhalable fraction) | |
| OEL STEL | 40 mg/m³ (inhalable fraction) | |
| Spain - Occupational Exposure Limits | | |
| VLA-ED (OEL TWA) | 10 mg/m³ | |
| United Kingdom - Occupational Exposure Limits | | |
| WEL TWA (OEL TWA) | 10 mg/m³ | |
| WEL STEL (OEL STEL) | 30 mg/m³ (calculated) | |
| Switzerland - Occupational Exposure Limits | | |
| MAK (OEL TWA) | 10 mg/m³ (no elevated carcinogenic risk by keeping the MAK-value-aerosol, inhalable dust, vapour) | |
| KZGW (OEL STEL) | 40 mg/m³ (no increased cancer risk by adhering to TWA values-aerosol, inhalable dust, vapour) | |
| OEL chemical category | Category C1B carcinogen carcinogenic with threshold value | |
| USA - ACGIH - Occupational Exposure Limits | | |
| ACGIH OEL TWA | 2 mg/m³ (inhalable fraction and vapor) | |
| ACGIH chemical category | Not Classifiable as a Human Carcinogen | |
| butyric acid (107-92-6) | | |
| Bulgaria - Occupational Exposure Limits | | |
| OEL TWA | 10 mg/m³ | |
| Latvia - Occupational Exposure Limits | | |
| OEL TWA | 10 mg/m³ | |
| Lithuania - Occupational Exposure Limits | | |
| IPRV (OEL TWA) | 10 mg/m³ | |
| Romania - Occupational Exposure Limits | | |
| OEL TWA | 15 mg/m³ | |
| | 4 ppm | |
| OEL STEL | 30 mg/m³ | |
| | 8 ppm | |
| Isoamyl alcohol (123-51-3) | | |
| Austria - Occupational Exposure Limits | | |
| MAK (OEL TWA) | 18 mg/m³ | |
| | 5 ppm | |

Safety Data Sheet

| Isoamyl alcohol (123-51-3) | | | | |
|---|---|--|--|--|
| MAK (OEL STEL) | 37 mg/m³ | | | |
| | 10 ppm | | | |
| Belgium - Occupational Exposure Limits | | | | |
| OEL TWA | 18 mg/m³ | | | |
| | 5 ppm | | | |
| OEL STEL | 37 mg/m³ | | | |
| | 10 ppm | | | |
| Bulgaria - Occupational Exposure Limits | | | | |
| OEL TWA | 18 mg/m³ | | | |
| | 5 ppm | | | |
| OEL STEL | 37 mg/m³ | | | |
| | 10 ppm | | | |
| Croatia - Occupational Exposure Limits | | | | |
| GVI (OEL TWA) | 18 mg/m³ 366 mg/m³ (regulated under 3-Methyl-1-butanol (3-Methyl-1-butanol) | | | |
| | 5 ppm 100 ppm (regulated under 3-Methyl-1-butanol (3-Methyl-1-butanol) | | | |
| KGVI (OEL STEL) | 37 mg/m³ 458 mg/m³ (regulated under 3-Methyl-1-butanol (3-Methyl-1-butanol) | | | |
| | 10 ppm 125 ppm (regulated under 3-Methyl-1-butanol (3-Methyl-1-butanol) | | | |
| Cyprus - Occupational Exposure Limits | | | | |
| OEL TWA | 18 mg/m³ | | | |
| | 5 ppm | | | |
| OEL STEL | 37 mg/m³ | | | |
| | 10 ppm | | | |
| Czech Republic - Occupational Exposure Limits | | | | |
| PEL (OEL TWA) | 18 mg/m³ | | | |
| Denmark - Occupational Exposure Limits | | | | |
| OEL TWA | 18 mg/m³ (Pentanol, all isomers) | | | |
| | 5 ppm (Pentanol, all isomers) | | | |
| OEL STEL | 37 mg/m³ | | | |
| | 10 ppm | | | |
| Estonia - Occupational Exposure Limits | | | | |
| OEL TWA | 18 mg/m³ | | | |
| | 5 ppm | | | |
| OEL STEL | 37 mg/m³ | | | |
| | 10 ppm | | | |
| Finland - Occupational Exposure Limits | | | | |
| HTP (OEL TWA) | 18 mg/m³ (Pentanol) | | | |

Safety Data Sheet

| Isoamyl alcohol (123-51-3) | | | |
|---|---|--|--|
| | 5 ppm (Pentanol) | | |
| HTP (OEL STEL) | 37 mg/m³ | | |
| | 10 ppm | | |
| France - Occupational Exposure Limits | | | |
| VME (OEL TWA) | 18 mg/m³ (restrictive limit) | | |
| | 5 ppm (restrictive limit) | | |
| VLE (OEL C/STEL) | 37 mg/m³ (restrictive limit) | | |
| | 10 ppm (restrictive limit) | | |
| Germany - Occupational Exposure Limits (TRGS 90 | 00) | | |
| AGW (OEL TWA) | 73 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) | | |
| | 20 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) | | |
| Greece - Occupational Exposure Limits | | | |
| OEL TWA | 18 mg/m³ | | |
| | 5 ppm | | |
| OEL STEL | 37 mg/m³ | | |
| | 10 ppm | | |
| Hungary - Occupational Exposure Limits | | | |
| AK (OEL TWA) | 18 mg/m³ | | |
| CK (OEL STEL) | 37 mg/m³ | | |
| Ireland - Occupational Exposure Limits | | | |
| OEL TWA | 18 mg/m³ | | |
| | 5 ppm | | |
| OEL STEL | 10 mg/m³ | | |
| | 37 ppm | | |
| Italy - Occupational Exposure Limits | | | |
| OEL TWA | 18 mg/m³ | | |
| | 5 ppm | | |
| OEL STEL | 37 mg/m³ | | |
| | 10 ppm | | |
| Latvia - Occupational Exposure Limits | | | |
| OEL TWA | 18 mg/m³ | | |
| | 5 ppm | | |
| Lithuania - Occupational Exposure Limits | | | |
| IPRV (OEL TWA) | 18 mg/m³ | | |
| | 5 ppm | | |
| TPRV (OEL STEL) | 37 mg/m³ | | |
| | 10 ppm | | |

Safety Data Sheet

| Luxembourg - Occupational Exposure Limits DEL TWA | | |
|---|-----------------------------------|--|
| OFI TWA | | |
| /== · · · / / · | 18 mg/m³ | |
| ! | 5 ppm | |
| DEL STEL ; | 37 mg/m³ | |
| | 10 ppm | |
| Netherlands - Occupational Exposure Limits | | |
| rGG-8u (OEL TWA) | 18 mg/m³ | |
| ! | 5 ppm | |
| rGG-15min (OEL STEL) | 37 mg/m³ | |
| | 10 ppm | |
| Poland - Occupational Exposure Limits | | |
| NDS (OEL TWA) | 18 mg/m³ | |
| NDSCh (OEL STEL) | 37 mg/m³ | |
| Portugal - Occupational Exposure Limits | | |
| DEL TWA | 18 mg/m³ (indicative limit value) | |
| 1 | 5 ppm (indicative limit value) | |
| DEL STEL : | 37 mg/m³ (indicative limit value) | |
| | 10 ppm (indicative limit value) | |
| Romania - Occupational Exposure Limits | | |
| DEL TWA | 18 mg/m³ | |
| ! | 5 ppm | |
| DEL STEL : | 37 mg/m³ | |
| | 10 ppm | |
| Slovakia - Occupational Exposure Limits | | |
| NPHV (OEL TWA) | 18 mg/m³ | |
| ! | 5 ppm | |
| NPHV (OEL C) | 37 mg/m³ | |
| Slovenia - Occupational Exposure Limits | | |
| DEL TWA | 18 mg/m³ | |
| ! | 5 ppm | |
| DEL STEL ; | 37 mg/m³ | |
| | 10 ppm | |
| Spain - Occupational Exposure Limits | | |
| /LA-ED (OEL TWA) | 18 mg/m³ | |
| <u>'</u> | 5 ppm | |
| /LA-EC (OEL STEL) | 37 mg/m³ | |
| | 10 ppm | |
| Sweden - Occupational Exposure Limits | | |
| NGV (OEL TWA) | 18 mg/m³ | |

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Isoamyl alcohol (123-51-3) | | | |
|---|---|--|--|
| | 5 ppm | | |
| KGV (OEL STEL) | 37 mg/m³ | | |
| | 10 ppm | | |
| OEL chemical category | Skin notation | | |
| United Kingdom - Occupational Exposure Limits | | | |
| WEL TWA (OEL TWA) | 366 mg/m³ | | |
| | 100 ppm | | |
| WEL STEL (OEL STEL) | 458 mg/m³ | | |
| | 125 ppm | | |
| Norway - Occupational Exposure Limits | | | |
| Grenseverdi (OEL TWA) | 18 mg/m³ | | |
| | 5 ppm | | |
| Korttidsverdi (OEL STEL) | 37 mg/m³ (value from the regulation) | | |
| | 10 ppm (value from the regulation) | | |
| OEL chemical category | Skin notation | | |
| Switzerland - Occupational Exposure Limits | | | |
| MAK (OEL TWA) | 75 mg/m³ (Pentanol all isomers except 3-Methyl-1-butanol) | | |
| | 20 ppm (Pentanol all isomers except 3-Methyl-1-butanol) | | |
| KZGW (OEL STEL) | 150 mg/m³ (Pentanol (mixture of isomers) except 3-Methyl-1-butanol) | | |
| | 40 ppm (Pentanol (mixture of isomers) except 3-Methyl-1-butanol) | | |
| USA - ACGIH - Occupational Exposure Limits | | | |
| ACGIH OEL TWA | 100 ppm | | |
| ACGIH OEL STEL | 125 ppm | | |

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Conforms to standard.

Odour : characteristic. Odour threshold : Not available : Not applicable Melting point Freezing point : Not available : Not available Boiling point Flammability : Not applicable Lower explosion limit : Not available Upper explosion limit : Not available : > 93.3 °C Flash point Auto-ignition temperature : Not available Decomposition temperature : Not available : Not available Viscosity, kinematic : Not available Solubility : Not available

Vapour pressure : 0.014241121 mm Hg (calculated value)

: Not available

Vapour pressure at 50°C : Not available
Density : Not available
Relative density : Not available
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

Partition coefficient n-octanol/water (Log Kow)

9/23/2024 (Issue date) EN (English) 19/28

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 4.95 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

LD50 dermal rabbit

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

| Acute toxicity (initialation) | Not classified | | | |
|---|----------------------------------|--|--|--|
| MAPLE SYRUP & PANCAKES FR98009 | | | | |
| ATE CLP (oral) | 567.86 mg/kg bodyweight | | | |
| benzyl benzoate (120-51-4) | | | | |
| LD50 oral rat | > 2000 mg/kg (Source: ECHA_API) | | | |
| D50 oral 1160 mg/kg bodyweight | | | | |
| LD50 dermal rabbit | it 4000 mg/kg (Source: NLM_CIP) | | | |
| Vanillin (121-33-5) | | | | |
| LD50 dermal rabbit | > 5010 mg/kg (Source: OECD_SIDS) | | | |
| LD50 dermal | 2600 mg/kg bodyweight | | | |
| 1,2-Cyclopentanedione, 3-methyl- (765-70-8) | | | | |
| LD50 oral | 1067 mg/kg bodyweight | | | |
| 1,2-Propanediol (57-55-6) | | | | |
| LD50 oral rat | 20 g/kg (Source: NLM_CIP) | | | |
| | | | | |

20800 mg/kg (Source: NLM CIP)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Ethyl vanillin (121-32-4) | | | |
|--|--|--|--|
| LD50 oral rat | 1590 mg/kg (Source: NLM_CIP) | | |
| LD50 oral | 3000 mg/kg bodyweight | | |
| LD50 dermal rat | > 2000 mg/kg (Source: ECHA_API) | | |
| pentyl acetate (628-63-7) | | | |
| LD50 oral rat | 6500 mg/kg (Source: NLM_HSDB) | | |
| Butylated hydroxytoluene (BHT) crystals (128 | -37-0) | | |
| LD50 oral rat | > 2930 mg/kg (Source: EPA_HPV) | | |
| LD50 dermal rat | > 2000 mg/kg (Source: JAPAN_GHS) | | |
| butyric acid (107-92-6) | | | |
| LD50 oral rat | 2 g/kg (Source: NLM_CIP) | | |
| LD50 oral | 1630 mg/kg bodyweight | | |
| LD50 dermal rabbit | 530 mg/kg (Source: NLM_HSDB) | | |
| Isoamyl alcohol (123-51-3) | | | |
| LD50 oral rat | 5770 mg/kg (Source: AU_WES) | | |
| LD50 oral | 4000 mg/kg bodyweight | | |
| LD50 dermal rabbit | 3250 mg/kg (Source: JAPAN_GHS) | | |
| LD50 dermal | 3216 mg/kg bodyweight | | |
| LC50 Inhalation - Rat [ppm] | > 2000 ppm (Exposure time: 8 h Source: AU_WES) | | |
| Skin corrosion/irritation : | Not classified | | |
| Serious eye damage/irritation : | Not classified | | |
| Respiratory or skin sensitisation : | May cause an allergic skin reaction. | | |
| Germ cell mutagenicity : | Not classified | | |
| Carcinogenicity : | Not classified | | |
| Butylated hydroxytoluene (BHT) crystals (128-37-0) | | | |
| IARC group | 3 - Not classifiable | | |
| Reproductive toxicity : | Not classified | | |
| STOT-single exposure : | Not classified | | |
| Isoamyl alcohol (123-51-3) | | | |
| STOT-single exposure | May cause respiratory irritation. | | |
| STOT-repeated exposure : | Not classified | | |
| Aspiration hazard : | Not classified | | |
| benzyl benzoate (120-51-4) | | | |
| Viscosity, kinematic | 7.456 mm²/s | | |
| | | | |

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms

: Based on available data, the classification criteria are not met, Harmful if swallowed.

9/23/2024 (Issue date) EN (English) 21/28

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Very toxic to aquatic life.

(acute)

Hazardous to the aquatic environment, long-term : Toxic to aquatic life with long lasting effects.

(chronic)

| (chronic) | | | | |
|--|--|--|--|--|
| benzyl benzoate (120-51-4) | | | | |
| LC50 - Fish [1] | 2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA) | | | |
| NOEC (chronic) | 0.168 mg/l | | | |
| Vanillin (121-33-5) | | | | |
| LC50 - Fish [1] | 53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA) | | | |
| LC50 - Fish [2] | 88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA) | | | |
| NOEC (acute) | 10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight]) | | | |
| 1,2-Propanediol (57-55-6) | | | | |
| LC50 - Fish [1] | 51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID) | | | |
| LC50 - Fish [2] | 41 – 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA) | | | |
| EC50 - Crustacea [1] | > 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) | | | |
| EC50 96h - Algae [1] | 19000 mg/l (Species: Pseudokirchneriella subcapitata) | | | |
| Ethyl vanillin (121-32-4) | | | | |
| LC50 - Fish [1] | 81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA) | | | |
| pentyl acetate (628-63-7) | | | | |
| LC50 - Fish [1] | 650 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) | | | |
| Butylated hydroxytoluene (BHT) crystals (128 | 3-37-0) | | | |
| EC50 72h - Algae [1] | 6 mg/l (Species: Pseudokirchneriella subcapitata) | | | |
| EC50 72h - Algae [2] | > 0.42 mg/l (Species: Desmodesmus subspicatus) | | | |
| butyric acid (107-92-6) | | | | |
| EC50 72h - Algae [1] | 46.7 mg/l (Species: Desmodesmus subspicatus) | | | |
| Isoamyl alcohol (123-51-3) | | | | |
| LC50 - Fish [1] | 700 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: ECHA) | | | |
| EC50 - Crustacea [1] | 260 mg/l (Exposure time: 48 h - Species: Daphnia magna) | | | |
| EC50 72h - Algae [1] | 493 mg/l (Species: Desmodesmus subspicatus) | | | |
| EC50 96h - Algae [1] | 181 mg/l (Species: Desmodesmus subspicatus) | | | |
| | I e e e e e e e e e e e e e e e e e e e | | | |

12.2. Persistence and degradability

| MAPLE SYRUP & PANCAKES FR98009 | | |
|---|--|--|
| Persistence and degradability Not established. | | |
| benzyl benzoate (120-51-4) | | |
| Persistence and degradability May cause long-term adverse effects in the environment. | | |

9/23/2024 (Issue date) EN (English) 22/28

Safety Data Sheet

| Vanillin (121-33-5) | | | | |
|--|--|--|--|--|
| Persistence and degradability | Rapidly degradable | | | |
| 1,2-Cyclopentanedione, 3-methyl- (765-70-8) | | | | |
| Persistence and degradability | Rapidly degradable | | | |
| 1,2-Propanediol (57-55-6) | | | | |
| Persistence and degradability | Rapidly degradable | | | |
| Ethyl vanillin (121-32-4) | | | | |
| Persistence and degradability | Rapidly degradable | | | |
| pentyl acetate (628-63-7) | | | | |
| Persistence and degradability | Rapidly degradable | | | |
| isopentyl acetate (123-92-2) | | | | |
| Persistence and degradability | Rapidly degradable | | | |
| Butylated hydroxytoluene (BHT) crystals (128 | 37-0) | | | |
| Persistence and degradability | Rapidly degradable | | | |
| butyric acid (107-92-6) | | | | |
| Persistence and degradability | Rapidly degradable | | | |
| Isoamyl alcohol (123-51-3) | | | | |
| Persistence and degradability | Rapidly degradable | | | |
| 12.3. Bioaccumulative potential | | | | |
| 12.3. Bioaccumulative potential | | | | |
| 12.3. Bioaccumulative potential MAPLE SYRUP & PANCAKES FR98009 | | | | |
| | Not established. | | | |
| MAPLE SYRUP & PANCAKES FR98009 | Not established. | | | |
| MAPLE SYRUP & PANCAKES FR98009 Bioaccumulative potential | Not established. 3.97 (at 25 °C) | | | |
| MAPLE SYRUP & PANCAKES FR98009 Bioaccumulative potential benzyl benzoate (120-51-4) | | | | |
| MAPLE SYRUP & PANCAKES FR98009 Bioaccumulative potential benzyl benzoate (120-51-4) Partition coefficient n-octanol/water (Log Pow) | 3.97 (at 25 °C) | | | |
| MAPLE SYRUP & PANCAKES FR98009 Bioaccumulative potential benzyl benzoate (120-51-4) Partition coefficient n-octanol/water (Log Pow) Bioaccumulative potential | 3.97 (at 25 °C) | | | |
| MAPLE SYRUP & PANCAKES FR98009 Bioaccumulative potential benzyl benzoate (120-51-4) Partition coefficient n-octanol/water (Log Pow) Bioaccumulative potential Vanillin (121-33-5) | 3.97 (at 25 °C) Not established. | | | |
| MAPLE SYRUP & PANCAKES FR98009 Bioaccumulative potential benzyl benzoate (120-51-4) Partition coefficient n-octanol/water (Log Pow) Bioaccumulative potential Vanillin (121-33-5) Partition coefficient n-octanol/water (Log Pow) | 3.97 (at 25 °C) Not established. | | | |
| MAPLE SYRUP & PANCAKES FR98009 Bioaccumulative potential benzyl benzoate (120-51-4) Partition coefficient n-octanol/water (Log Pow) Bioaccumulative potential Vanillin (121-33-5) Partition coefficient n-octanol/water (Log Pow) 1,2-Propanediol (57-55-6) | 3.97 (at 25 °C) Not established. 1.23 (at 22 °C) | | | |
| MAPLE SYRUP & PANCAKES FR98009 Bioaccumulative potential benzyl benzoate (120-51-4) Partition coefficient n-octanol/water (Log Pow) Bioaccumulative potential Vanillin (121-33-5) Partition coefficient n-octanol/water (Log Pow) 1,2-Propanediol (57-55-6) BCF - Fish [1] | 3.97 (at 25 °C) Not established. 1.23 (at 22 °C) (1 dimensionless) | | | |
| MAPLE SYRUP & PANCAKES FR98009 Bioaccumulative potential benzyl benzoate (120-51-4) Partition coefficient n-octanol/water (Log Pow) Bioaccumulative potential Vanillin (121-33-5) Partition coefficient n-octanol/water (Log Pow) 1,2-Propanediol (57-55-6) BCF - Fish [1] Partition coefficient n-octanol/water (Log Pow) | 3.97 (at 25 °C) Not established. 1.23 (at 22 °C) (1 dimensionless) | | | |
| MAPLE SYRUP & PANCAKES FR98009 Bioaccumulative potential benzyl benzoate (120-51-4) Partition coefficient n-octanol/water (Log Pow) Bioaccumulative potential Vanillin (121-33-5) Partition coefficient n-octanol/water (Log Pow) 1,2-Propanediol (57-55-6) BCF - Fish [1] Partition coefficient n-octanol/water (Log Pow) Ethyl vanillin (121-32-4) | 3.97 (at 25 °C) Not established. 1.23 (at 22 °C) (1 dimensionless) -1.07 (at 20.5 °C (at pH >=6.2-<=6.4) | | | |
| MAPLE SYRUP & PANCAKES FR98009 Bioaccumulative potential benzyl benzoate (120-51-4) Partition coefficient n-octanol/water (Log Pow) Bioaccumulative potential Vanillin (121-33-5) Partition coefficient n-octanol/water (Log Pow) 1,2-Propanediol (57-55-6) BCF - Fish [1] Partition coefficient n-octanol/water (Log Pow) Ethyl vanillin (121-32-4) Partition coefficient n-octanol/water (Log Pow) | 3.97 (at 25 °C) Not established. 1.23 (at 22 °C) (1 dimensionless) -1.07 (at 20.5 °C (at pH >=6.2-<=6.4) | | | |
| MAPLE SYRUP & PANCAKES FR98009 Bioaccumulative potential benzyl benzoate (120-51-4) Partition coefficient n-octanol/water (Log Pow) Bioaccumulative potential Vanillin (121-33-5) Partition coefficient n-octanol/water (Log Pow) 1,2-Propanediol (57-55-6) BCF - Fish [1] Partition coefficient n-octanol/water (Log Pow) Ethyl vanillin (121-32-4) Partition coefficient n-octanol/water (Log Pow) isopentyl acetate (123-92-2) | 3.97 (at 25 °C) Not established. 1.23 (at 22 °C) (1 dimensionless) -1.07 (at 20.5 °C (at pH >=6.2-<=6.4) 1.61 (at 25 °C) 2.7 (at 35 °C) | | | |
| MAPLE SYRUP & PANCAKES FR98009 Bioaccumulative potential benzyl benzoate (120-51-4) Partition coefficient n-octanol/water (Log Pow) Bioaccumulative potential Vanillin (121-33-5) Partition coefficient n-octanol/water (Log Pow) 1,2-Propanediol (57-55-6) BCF - Fish [1] Partition coefficient n-octanol/water (Log Pow) Ethyl vanillin (121-32-4) Partition coefficient n-octanol/water (Log Pow) isopentyl acetate (123-92-2) Partition coefficient n-octanol/water (Log Pow) | 3.97 (at 25 °C) Not established. 1.23 (at 22 °C) (1 dimensionless) -1.07 (at 20.5 °C (at pH >=6.2-<=6.4) 1.61 (at 25 °C) 2.7 (at 35 °C) | | | |

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| butyric acid (107-92-6) | | |
|--|------------------|--|
| Partition coefficient n-octanol/water (Log Pow) 1.1 (at 25 °C (at pH 3) | | |
| Isoamyl alcohol (123-51-3) | | |
| Partition coefficient n-octanol/water (Log Pow) | 1.35 (at pH 6.5) | |

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information

: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

Product/Packaging disposal recommendations

Ecological information

HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/national laws and regulations.
- : Avoid release to the environment.
- : HP6 "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.

HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

| ADR | IMDG | IATA | ADN | RID | |
|--|---|--|---|---|--|
| 14.1. UN number or ID number | | | | | |
| UN 3082 | UN 3082 | UN 3082 | UN 3082 | UN 3082 | |
| 14.2. UN proper shippin | g name | | | | |
| ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate) | Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate) | |
| Transport document descr | iption | | | | |
| UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, (-) | UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, MARINE POLLUTANT | UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate), 9, III | UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III | UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III | |

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| ADR | IMDG | IATA | ADN | RID |
|--|--|--|--|--|
| 14.3. Transport hazard class(es) | | | | |
| 9 | 9 | 9 | 9 | 9 |
| ************************************** | ************************************** | ************************************** | ************************************** | ************************************** |
| 14.4. Packing group | | | | |
| III | III | III | III | III |
| 14.5. Environmental hazards | | | | |
| Dangerous for the environment: Yes | Dangerous for the environment: Yes Marine pollutant: Yes | Dangerous for the environment: Yes | Dangerous for the environment: Yes | Dangerous for the environment: Yes |
| No supplementary information available | | | | |

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6

Special provisions (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 90

Orange plates :

90 3082

Tunnel restriction code (ADR) : EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : LP01, P001

Special packing provisions (IMDG) : PP1

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP29

EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Carriage permitted (ADN) : T

Equipment required (ADN) : PP

Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV

Transport category (RID) : 3

Special provisions for carriage – Packages (RID) : W12

Special provisions for carriage - Loading, unloading : CW13, CW31

and handling (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

| EU restriction list (REACH Annex XVII) | | |
|--|--|---|
| Reference code | Applicable on | Entry title or description |
| 3(a) | pentyl acetate ; isopentyl acetate ; Isoamyl alcohol | Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F |
| 3(b) | MAPLE SYRUP & PANCAKES FR98009; benzyl benzoate; butyric acid; Isoamyl alcohol | Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10 |

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| EU restriction list (REACH Annex XVII) | | | |
|--|---|--|--|
| Reference code | Applicable on | Entry title or description | |
| 3(c) | MAPLE SYRUP & PANCAKES FR98009; benzyl benzoate | Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1 | |
| 40. | pentyl acetate ; isopentyl acetate ; Isoamyl alcohol | Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not. | |

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 4.95 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

| Occupational diseases | | |
|-----------------------|---|--|
| Code | Description | |
| RG 84 | Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide | |

Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic

: None of the components are listed

environment

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen : None of the components are listed SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

9/23/2024 (Issue date) EN (English) 27/28

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SZW-lijst van reprotoxische stoffen – : None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information : None.

| Full text of H- and EUH-statements: | | |
|-------------------------------------|--|--|
| Acute Tox. 4 (Oral) | Acute toxicity (oral), Category 4 | |
| Aquatic Acute 1 | Hazardous to the aquatic environment – Acute Hazard, Category 1 | |
| Aquatic Chronic 1 | Hazardous to the aquatic environment – Chronic Hazard, Category 1 | |
| Aquatic Chronic 2 | Hazardous to the aquatic environment – Chronic Hazard, Category 2 | |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 | |
| Flam. Liq. 3 | Flammable liquids, Category 3 | |
| H226 | Flammable liquid and vapour. | |
| H302 | Harmful if swallowed. | |
| H314 | Causes severe skin burns and eye damage. | |
| H315 | Causes skin irritation. | |
| H317 | May cause an allergic skin reaction. | |
| H319 | Causes serious eye irritation. | |
| H335 | May cause respiratory irritation. | |
| H400 | Very toxic to aquatic life. | |
| H410 | Very toxic to aquatic life with long lasting effects. | |
| H411 | Toxic to aquatic life with long lasting effects. | |
| Skin Corr. 1B | Skin corrosion/irritation, Category 1, Sub-Category 1B | |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 | |
| Skin Sens. 1 | Skin sensitisation, Category 1 | |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation | |

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU